



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** SHADE SYSTEM 2K SEALER - WHITE

### Other means of identification

**Product Code** AV-8321-G

**Recommended use** Automotive Refinish Primer

### Manufacturer/Importer/Supplier/Distributor information

#### Manufacturer

**Company name** Aftermarket Auto Parts Alliance

**Address** 2706 Treble Creek  
San Antonio, Texas 78258  
United States

**Telephone** General Assistance 210-492-4868

**E-mail** product@alliance1.com

**Contact person** Dan Rader

**Emergency phone number** Emergency Contact 210-408-4343

## 2. Hazard(s) identification

|                              |  |             |
|------------------------------|--|-------------|
| <b>Physical hazards</b>      | Flammable liquids                                      | Category 2  |
| <b>Health hazards</b>        | Acute toxicity, oral                                   | Category 4  |
|                              | Acute toxicity, inhalation                             | Category 3  |
|                              | Serious eye damage/eye irritation                      | Category 2B |
|                              | Germ cell mutagenicity                                 | Category 1B |
|                              | Carcinogenicity  | Category 1B |
|                              | Reproductive toxicity (the unborn child)               | Category 2  |
|                              | Specific target organ toxicity, repeated exposure      | Category 1  |
| <b>Environmental hazards</b> | Hazardous to the aquatic environment, acute hazard     | Category 2  |
|                              | Hazardous to the aquatic environment, long-term hazard | Category 3  |
| <b>OSHA defined hazards</b>  | Not classified.  |             |

### Label elements



**Signal word** Danger

**Hazard statement** Highly flammable liquid and vapor. Harmful if swallowed. Causes eye irritation. Toxic if inhaled. May cause genetic defects. May cause cancer. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

### Precautionary statement

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

|  |   |
|--|---|
| <b>Response</b>                                  | If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish. |
| <b>Storage</b>                                   | Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.  |
| <b>Disposal</b>                                  | Dispose of contents/container in accordance with local/regional/national/international regulations.   |
| <b>Hazard(s) not otherwise classified (HNOC)</b> | Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.   |
| <b>Supplemental information</b>                  | 63.18% of the mixture consists of component(s) of unknown acute oral toxicity. 75.87% of the mixture consists of component(s) of unknown acute inhalation toxicity. 92.3% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 92.3% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.   |

### 3. Composition/information on ingredients

#### Mixtures

| Chemical name                            | Common name and synonyms | CAS number | %         |
|--|--------------------------|------------|-----------|
| Titanium dioxide                         |                          | 13463-67-7 | 30 to <40 |
| 2-Heptanone                              |                          | 110-43-0   | 10 to <20 |
| Talc                                     |                          | 14807-96-6 | 5 to <10  |
| 2-pentanone                              |                          | 107-87-9   | 1 to <5   |
| 4-Methyl-2-pentanone                     |                          | 108-10-1   | 1 to <5   |
| Aluminum hydroxide                       |                          | 21645-51-2 | 1 to <5   |
| Ethyl 3-ethoxypropionate                 |                          | 763-69-9   | 1 to <5   |
| n-butyl acetate                          |                          | 123-86-4   | 1 to <5   |
| Silicon dioxide                          |                          | 7631-86-9  | 1 to <5   |
| Xylene                                   |                          | 1330-20-7  | 1 to <5   |
| 1,2-Dimethylbenzene                      |                          | 95-47-6    | 0.1 to <1 |
| Ethyl benzene                            |                          | 100-41-4   | 0.1 to <1 |
| Toluene                                  |                          | 108-88-3   | 0.1 to <1 |
| VM & P NAPHTHA                           |                          | 8032-32-4  | 0.1 to <1 |
| Other components below reportable levels |                          |            | 20 to <30 |

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

|   |  |
|---|--|
| <b>Inhalation</b>   | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician. |
| <b>Skin contact</b>   | Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.   |
| <b>Eye contact</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.  |
| <b>Ingestion</b>  | Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.  |
| <b>Most important symptoms/effects, acute and delayed</b>                     | Headache. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Prolonged exposure may cause chronic effects.   |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.  |

|  |   |
|--|---|
| <b>General information</b>   | Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.  |
| <b>5. Fire-fighting measures</b>   |   |
| <b>Suitable extinguishing media</b>  | Alcohol resistant foam. Water fog. Carbon dioxide (CO <sub>2</sub> ). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.  |
| <b>Unsuitable extinguishing media</b>                                      | Do not use water jet as an extinguisher, as this will spread the fire.  |
| <b>Specific hazards arising from the chemical</b>                          | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.  |
| <b>Special protective equipment and precautions for firefighters</b>       | Self-contained breathing apparatus and full protective clothing must be worn in case of fire.   |
| <b>Fire fighting equipment/instructions</b>                                | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.  |
| <b>Specific methods</b>  | Use standard firefighting procedures and consider the hazards of other involved materials.  |
| <b>General fire hazards</b>  | Highly flammable liquid and vapor.  |
| <b>6. Accidental release measures</b>                                      |   |
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.  |
| <b>Methods and materials for containment and cleaning up</b>               | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.<br><br>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.<br><br>Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. |
| <b>Environmental precautions</b>   | Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.  |

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

### Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components                          | Type | Value                            | Form        |
|-------------------------------------|------|----------------------------------|-------------|
| 1,2-Dimethylbenzene (CAS 95-47-6)   | PEL  | 435 mg/m <sup>3</sup>            |             |
| 2-Heptanone (CAS 110-43-0)          | PEL  | 100 ppm<br>465 mg/m <sup>3</sup> |             |
| 2-pentanone (CAS 107-87-9)          | PEL  | 100 ppm<br>700 mg/m <sup>3</sup> |             |
| 4-Methyl-2-pentanone (CAS 108-10-1) | PEL  | 200 ppm<br>410 mg/m <sup>3</sup> |             |
| Ethyl benzene (CAS 100-41-4)        | PEL  | 100 ppm<br>435 mg/m <sup>3</sup> |             |
| n-butyl acetate (CAS 123-86-4)      | PEL  | 100 ppm<br>710 mg/m <sup>3</sup> |             |
| Titanium dioxide (CAS 13463-67-7)   | PEL  | 150 ppm<br>15 mg/m <sup>3</sup>  | Total dust. |
| Xylene (CAS 1330-20-7)              | PEL  | 435 mg/m <sup>3</sup><br>100 ppm |             |

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

| Components             | Type    | Value   |
|------------------------|---------|---------|
| Toluene (CAS 108-88-3) | Ceiling | 300 ppm |
|                        | TWA     | 200 ppm |

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

| Components                      | Type | Value   | Form                                      |
|---------------------------------|------|---|---|
| Silicon dioxide (CAS 7631-86-9) | TWA  | 0.8 mg/m3   |   |
| Talc (CAS 14807-96-6)           | TWA  | 20 mppcf<br>0.3 mg/m3<br>0.1 mg/m3<br>20 mppcf<br>2.4 mppcf | Total dust.<br>Respirable.<br>Respirable. |

**US. ACGIH Threshold Limit Values**

| Components                          | Type | Value    | Form                 |
|-------------------------------------|------|----------|----------------------|
| 1,2-Dimethylbenzene (CAS 95-47-6)   | STEL | 150 ppm  |                      |
|                                     | TWA  | 100 ppm  |                      |
| 2-Heptanone (CAS 110-43-0)          | TWA  | 50 ppm   |                      |
| 2-pentanone (CAS 107-87-9)          | STEL | 150 ppm  |                      |
| 4-Methyl-2-pentanone (CAS 108-10-1) | STEL | 75 ppm   |                      |
|                                     | TWA  | 20 ppm   |                      |
| Aluminum hydroxide (CAS 21645-51-2) | TWA  | 1 mg/m3  | Respirable fraction. |
| Ethyl benzene (CAS 100-41-4)        | TWA  | 20 ppm   |                      |
| n-butyl acetate (CAS 123-86-4)      | STEL | 200 ppm  |                      |
|                                     | TWA  | 150 ppm  |                      |
| Talc (CAS 14807-96-6)               | TWA  | 2 mg/m3  | Respirable fraction. |
| Titanium dioxide (CAS 13463-67-7)   | TWA  | 10 mg/m3 |                      |
| Toluene (CAS 108-88-3)              | TWA  | 20 ppm   |                      |
| Xylene (CAS 1330-20-7)              | STEL | 150 ppm  |                      |
|                                     | TWA  | 100 ppm  |                      |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components                          | Type | Value                           | Form |
|-------------------------------------|------|---------------------------------|------|
| 1,2-Dimethylbenzene (CAS 95-47-6)   | STEL | 655 mg/m3                       |      |
|                                     | TWA  | 150 ppm<br>435 mg/m3            |      |
| 2-Heptanone (CAS 110-43-0)          | TWA  | 100 ppm<br>465 mg/m3            |      |
| 2-pentanone (CAS 107-87-9)          | TWA  | 530 mg/m3                       |      |
| 4-Methyl-2-pentanone (CAS 108-10-1) | STEL | 150 ppm<br>300 mg/m3            |      |
|                                     | TWA  | 75 ppm<br>205 mg/m3             |      |
| Ethyl benzene (CAS 100-41-4)        | STEL | 50 ppm<br>545 mg/m3             |      |
|                                     | TWA  | 125 ppm<br>435 mg/m3<br>100 ppm |      |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components                      | Type    | Value      | Form        |
|---------------------------------|---------|------------|-------------|
| n-butyl acetate (CAS 123-86-4)  | STEL    | 950 mg/m3  |             |
|                                 |         | 200 ppm    |             |
|                                 | TWA     | 710 mg/m3  |             |
| Silicon dioxide (CAS 7631-86-9) | TWA     | 150 ppm    |             |
|                                 |         | 6 mg/m3    |             |
| Talc (CAS 14807-96-6)           | TWA     | 2 mg/m3    | Respirable. |
| Toluene (CAS 108-88-3)          | STEL    | 560 mg/m3  |             |
|                                 |         | 150 ppm    |             |
|                                 | TWA     | 375 mg/m3  |             |
| VM & P NAPHTHA (CAS 8032-32-4)  | Ceiling | 100 ppm    |             |
|                                 | TWA     | 1800 mg/m3 |             |
|                                 |         | 350 mg/m3  |             |

**Biological limit values**

**ACGIH Biological Exposure Indices**

| Components                          | Value     | Determinant                                   | Specimen            | Sampling Time |
|-------------------------------------|-----------|---|---------------------|---------------|
| 1,2-Dimethybenzene (CAS 95-47-6)    | 1.5 g/g   | Methylhippuric acids                          | Creatinine in urine | *             |
| 4-Methyl-2-pentanone (CAS 108-10-1) | 1 mg/l    | Methyl isobutyl ketone                        | Urine               | *             |
| Ethyl benzene (CAS 100-41-4)        | 0.15 g/g  | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | *             |
| Toluene (CAS 108-88-3)              | 0.3 mg/g  | o-Cresol, with hydrolysis                     | Creatinine in urine | *             |
|                                     | 0.03 mg/l | Toluene                                       | Urine               | *             |
|                                     | 0.02 mg/l | Toluene                                       | Blood               | *             |
| Xylene (CAS 1330-20-7)              | 1.5 g/g   | Methylhippuric acids                          | Creatinine in urine | *             |

\* - For sampling details, please see the source document.

**Exposure guidelines**

**US - California OELs: Skin designation**

Toluene (CAS 108-88-3) Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

Toluene (CAS 108-88-3) Skin designation applies.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection** Wear protective gloves.

**Other** Wear suitable protective clothing.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

|                |                   |
|----------------|-------------------|
| Physical state | Liquid.           |
| Form           | Liquid.           |
| Color          | Off-white Opaque. |

**Odor** Solvent.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** -31.9 °F (-35.5 °C) estimated

**Initial boiling point and boiling range** 304.7 °F (151.5 °C) estimated

**Flash point** 73.0 °F (22.8 °C) estimated

**Evaporation rate** Not available.

**Flammability (solid, gas)** Not applicable.

### Upper/lower flammability or explosive limits

**Flammability limit - lower (%)** 1.1 % estimated

**Flammability limit - upper (%)** 7.9 % estimated

**Explosive limit - lower (%)** Not available.

**Explosive limit - upper (%)** Not available.

**Vapor pressure** 2611.47 hPa estimated

**Vapor density** Not available.

**Relative density** Not available.

### Solubility(ies)

**Solubility (water)** Not available.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** 740 °F (393.33 °C) estimated

**Decomposition temperature** Not available.

**Viscosity** Not available.

### Other information

**Density** 12.25 lbs/gal

**Flammability class** Flammable IB estimated

**Percent volatile** 40.03 %

**Specific gravity** 1.47

**VOC** 4.3 lbs/gal Material  
4.5 lbs/gal Regulatory  
516 g/l Material  
545 g/l Regulatory

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** Hazardous polymerization does not occur.

**Conditions to avoid** Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials** Strong acids. Strong oxidizing agents. Halogens.

**Hazardous decomposition products** No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

|                     |  |
|---------------------|--|
| <b>Inhalation</b>   | Toxic if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. |
| <b>Skin contact</b> | No adverse effects due to skin contact are expected.   |
| <b>Eye contact</b>  | Causes eye irritation.   |
| <b>Ingestion</b>    | Harmful if swallowed.  |

**Symptoms related to the physical, chemical and toxicological characteristics**  
Headache. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.

### Information on toxicological effects

**Acute toxicity** Toxic if inhaled. Harmful if swallowed.

| <b>Components</b>                   | <b>Species</b> | <b>Test Results</b> |
|-------------------------------------|----------------|---------------------|
| 1,2-Dimethylbenzene (CAS 95-47-6)   |                |                     |
| <b>Acute</b>                        |                |                     |
| <b>Dermal</b>                       |                |                     |
| LD50                                | Rabbit         | > 43 g/kg           |
| <b>Inhalation</b>                   |                |                     |
| LC50                                | Mouse          | 4600 ppm, 6 Hours   |
|                                     | Rat            | 6350 ppm, 4 Hours   |
| <b>Oral</b>                         |                |                     |
| LD50                                | Mouse          | 1590 mg/kg          |
|                                     | Rat            | 4300 mg/kg          |
| 2-Heptanone (CAS 110-43-0)          |                |                     |
| <b>Acute</b>                        |                |                     |
| <b>Dermal</b>                       |                |                     |
| LD50                                | Rabbit         | 12600 mg/kg         |
| <b>Oral</b>                         |                |                     |
| LD50                                | Mouse          | 730 mg/kg           |
|                                     | Rat            | 1.67 g/kg           |
| 2-pentanone (CAS 107-87-9)          |                |                     |
| <b>Acute</b>                        |                |                     |
| <b>Oral</b>                         |                |                     |
| LD50                                | Rat            | 3.73 g/kg           |
| 4-Methyl-2-pentanone (CAS 108-10-1) |                |                     |
| <b>Acute</b>                        |                |                     |
| <b>Dermal</b>                       |                |                     |
| LD50                                | Rabbit         | > 16000 mg/kg       |
| <b>Inhalation</b>                   |                |                     |
| LC50                                | Rat            | 8.2 mg/l, 4 Hours   |
| <b>Oral</b>                         |                |                     |
| LD50                                | Rat            | 2080 mg/kg          |
| Aluminum hydroxide (CAS 21645-51-2) |                |                     |
| <b>Acute</b>                        |                |                     |
| <b>Oral</b>                         |                |                     |
| LD50                                | Rat            | > 5000 mg/kg        |
| Ethyl benzene (CAS 100-41-4)        |                |                     |
| <b>Acute</b>                        |                |                     |
| <b>Dermal</b>                       |                |                     |
| LD50                                | Rabbit         | 17800 mg/kg         |



| Components                                | Species    | Test Results  |
|---|------------|---|
| <b>Oral</b><br>LD50                       | Rat        | 3500 mg/kg  |
| n-butyl acetate (CAS 123-86-4)            |            |   |
| <b>Acute</b><br><b>Inhalation</b><br>LC50 | Wistar rat | 160 mg/l, 4 Hours   |
| <b>Oral</b><br>LD50                       | Rat        | 14000 mg/kg   |
| Silicon dioxide (CAS 7631-86-9)           |            |   |
| <b>Acute</b><br><b>Oral</b><br>LD50       | Mouse      | > 15000 mg/kg   |
|   | Rat        | > 22500 mg/kg   |
| Toluene (CAS 108-88-3)                    |            |   |
| <b>Acute</b><br><b>Dermal</b><br>LD50     | Rabbit     | 12124 mg/kg<br>14.1 ml/kg                                     |
| <b>Inhalation</b><br>LC50                 | Mouse      | 5320 ppm, 8 Hours<br>400 ppm, 24 Hours                        |
|   | Rat        | 26700 ppm, 1 Hours<br>12200 ppm, 2 Hours<br>8000 ppm, 4 Hours |
| <b>Oral</b><br>LD50                       | Rat        | 2.6 g/kg  |
| VM & P NAPHTHA (CAS 8032-32-4)            |            |   |
| <b>Acute</b><br><b>Inhalation</b><br>LC50 | Rat        | 3400 mg/l, 4 Hours  |
| Xylene (CAS 1330-20-7)                    |            |   |
| <b>Acute</b><br><b>Dermal</b><br>LD50     | Rabbit     | > 43 g/kg   |
| <b>Inhalation</b><br>LC50                 | Mouse      | 3907 mg/l, 6 Hours  |
|   | Rat        | 6350 mg/l, 4 Hours  |
| <b>Oral</b><br>LD50                       | Mouse      | 1590 mg/kg  |
|   | Rat        | 3523 - 8600 mg/kg   |

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Causes eye irritation.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** May cause genetic defects.

**Carcinogenicity** May cause cancer.

## IARC Monographs. Overall Evaluation of Carcinogenicity

|                                     |   |
|-------------------------------------|---|
| 1,2-Dimethylbenzene (CAS 95-47-6)   | 3 Not classifiable as to carcinogenicity to humans. |
| 4-Methyl-2-pentanone (CAS 108-10-1) | 2B Possibly carcinogenic to humans.                 |
| Ethyl benzene (CAS 100-41-4)        | 2B Possibly carcinogenic to humans.                 |
| Silicon dioxide (CAS 7631-86-9)     | 3 Not classifiable as to carcinogenicity to humans. |
| Titanium dioxide (CAS 13463-67-7)   | 2B Possibly carcinogenic to humans.                 |
| Toluene (CAS 108-88-3)              | 3 Not classifiable as to carcinogenicity to humans. |
| Xylene (CAS 1330-20-7)              | 3 Not classifiable as to carcinogenicity to humans. |

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

|   |   |
|---|---|
| <b>Reproductive toxicity</b>                              | Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child. |
| <b>Specific target organ toxicity - single exposure</b>   | Not classified.   |
| <b>Specific target organ toxicity - repeated exposure</b> | Causes damage to organs through prolonged or repeated exposure.   |
| <b>Aspiration hazard</b>                                  | Not an aspiration hazard.   |
| <b>Chronic effects</b>                                    | Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.          |

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

| Components                          | Species | Test Results   |
|-------------------------------------|---------|--|
| 1,2-Dimethylbenzene (CAS 95-47-6)   |         |  |
| <b>Aquatic</b>                      |         |  |
| Crustacea                           | EC50    | Water flea (Daphnia magna) 0.78 - 2.51 mg/l, 48 hours                          |
| Fish                                | LC50    | Rainbow trout,donaldson trout (Oncorhynchus mykiss) 5.59 - 11.6 mg/l, 96 hours |
| 2-Heptanone (CAS 110-43-0)          |         |  |
| <b>Aquatic</b>                      |         |  |
| Fish                                | LC50    | Fathead minnow (Pimephales promelas) 126 - 137 mg/l, 96 hours                  |
| 2-pentanone (CAS 107-87-9)          |         |  |
| <b>Aquatic</b>                      |         |  |
| Fish                                | LC50    | Fathead minnow (Pimephales promelas) 1190 - 1290 mg/l, 96 hours                |
| 4-Methyl-2-pentanone (CAS 108-10-1) |         |  |
| <b>Aquatic</b>                      |         |  |
| Fish                                | LC50    | Fathead minnow (Pimephales promelas) 492 - 593 mg/l, 96 hours                  |
| Ethyl benzene (CAS 100-41-4)        |         |  |
| <b>Aquatic</b>                      |         |  |
| Crustacea                           | EC50    | Water flea (Daphnia magna) 1.37 - 4.4 mg/l, 48 hours                           |
| Fish                                | LC50    | Fathead minnow (Pimephales promelas) 7.5 - 11 mg/l, 96 hours                   |
| n-butyl acetate (CAS 123-86-4)      |         |  |
| <b>Aquatic</b>                      |         |  |
| Fish                                | LC50    | Fathead minnow (Pimephales promelas) 17 - 19 mg/l, 96 hours                    |
| Titanium dioxide (CAS 13463-67-7)   |         |  |
| <b>Aquatic</b>                      |         |  |
| Crustacea                           | EC50    | Water flea (Daphnia magna) > 1000 mg/l, 48 hours                               |
| Fish                                | LC50    | Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours                        |
| Toluene (CAS 108-88-3)              |         |  |
| <b>Aquatic</b>                      |         |  |
| Crustacea                           | EC50    | Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours                          |
| Fish                                | LC50    | Coho salmon,silver salmon (Oncorhynchus kisutch) 8.11 mg/l, 96 hours           |

| Components             | Species | Test Results                            |
|------------------------|---------|---|
| Xylene (CAS 1330-20-7) |         |   |
| <b>Aquatic</b>         |         |   |
| Fish                   | LC50    | Bluegill ( <i>Lepomis macrochirus</i> ) |
|                        |         | 7.711 - 9.591 mg/l, 96 hours            |

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

#### Bioaccumulative potential

##### Partition coefficient n-octanol / water (log Kow)

|                      |            |
|----------------------|------------|
| 1,2-Dimethylbenzene  | 3.12       |
| 2-Heptanone          | 1.98       |
| 2-pentanone          | 0.91       |
| 4-Methyl-2-pentanone | 1.31       |
| Ethyl benzene        | 3.15       |
| n-butyl acetate      | 1.78       |
| Toluene              | 2.73       |
| Xylene               | 3.12 - 3.2 |

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

#### DOT

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1263  |
| <b>UN proper shipping name</b>      | Paint, Paint Related Material   |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 3   |
| <b>Subsidiary risk</b>              | -   |
| <b>Label(s)</b>                     | 3   |
| <b>Packing group</b>                | II  |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Special provisions</b>           | IB2, T7, TP1, TP8, TP28   |
| <b>Packaging exceptions</b>         | 150   |
| <b>Packaging non bulk</b>           | 202   |
| <b>Packaging bulk</b>               | 242   |

#### IATA

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1263  |
| <b>UN proper shipping name</b>      | Paint, Paint Related Material   |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 3   |
| <b>Subsidiary risk</b>              | -   |
| <b>Packing group</b>                | II  |
| <b>Environmental hazards</b>        | No.   |
| <b>ERG Code</b>                     | 3H  |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |

**Other information**

**Passenger and cargo aircraft** Allowed.  
**Cargo aircraft only** Allowed.

**IMDG**

**UN number** UN1263  
**UN proper shipping name** Paint, Paint Related Material  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Packing group** II  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** F-E, S-E  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

**DOT**



**IATA; IMDG**



**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

|                                     |         |
|-------------------------------------|---------|
| 1,2-Dimethylbenzene (CAS 95-47-6)   | Listed. |
| 2-pentanone (CAS 107-87-9)          | Listed. |
| 4-Methyl-2-pentanone (CAS 108-10-1) | Listed. |
| Ethyl benzene (CAS 100-41-4)        | Listed. |
| n-butyl acetate (CAS 123-86-4)      | Listed. |
| Toluene (CAS 108-88-3)              | Listed. |
| Xylene (CAS 1330-20-7)              | Listed. |

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - Yes  
 Pressure Hazard - No  
 Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**

| Chemical name        | CAS number | % by wt.  |
|----------------------|------------|-----------|
| 4-Methyl-2-pentanone | 108-10-1   | 1 to <5   |
| Xylene               | 1330-20-7  | 1 to <5   |
| 1,2-Dimethylbenzene  | 95-47-6    | 0.1 to <1 |
| Ethyl benzene        | 100-41-4   | 0.1 to <1 |
| Toluene              | 108-88-3   | 0.1 to <1 |

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

1,2-Dimethylbenzene (CAS 95-47-6)  
 4-Methyl-2-pentanone (CAS 108-10-1)  
 Ethyl benzene (CAS 100-41-4)  
 Toluene (CAS 108-88-3)  
 Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

4-Methyl-2-pentanone (CAS 108-10-1) 6715  
 Toluene (CAS 108-88-3) 6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

4-Methyl-2-pentanone (CAS 108-10-1) 35 %WV  
 Toluene (CAS 108-88-3) 35 %WV

**DEA Exempt Chemical Mixtures Code Number**

4-Methyl-2-pentanone (CAS 108-10-1) 6715  
 Toluene (CAS 108-88-3) 594

**US state regulations****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

1,2-Dimethylbenzene (CAS 95-47-6)  
 4-Methyl-2-pentanone (CAS 108-10-1)  
 Ethyl benzene (CAS 100-41-4)  
 Talc (CAS 14807-96-6)  
 Titanium dioxide (CAS 13463-67-7)  
 Toluene (CAS 108-88-3)  
 VM & P NAPHTHA (CAS 8032-32-4)  
 Xylene (CAS 1330-20-7)

**US. Massachusetts RTK - Substance List**

1,2-Dimethylbenzene (CAS 95-47-6)  
 2-Heptanone (CAS 110-43-0)  
 2-pentanone (CAS 107-87-9)  
 4-Methyl-2-pentanone (CAS 108-10-1)  
 Ethyl benzene (CAS 100-41-4)  
 n-butyl acetate (CAS 123-86-4)  
 Silicon dioxide (CAS 7631-86-9)  
 Talc (CAS 14807-96-6)

Titanium dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**US. New Jersey Worker and Community Right-to-Know Act**

1,2-Dimethylbenzene (CAS 95-47-6)  
2-Heptanone (CAS 110-43-0)  
2-pentanone (CAS 107-87-9)  
4-Methyl-2-pentanone (CAS 108-10-1)  
Ethyl benzene (CAS 100-41-4)  
n-butyl acetate (CAS 123-86-4)  
Silicon dioxide (CAS 7631-86-9)  
Talc (CAS 14807-96-6)  
Titanium dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
VM & P NAPHTHA (CAS 8032-32-4)  
Xylene (CAS 1330-20-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

1,2-Dimethylbenzene (CAS 95-47-6)  
2-Heptanone (CAS 110-43-0)  
2-pentanone (CAS 107-87-9)  
4-Methyl-2-pentanone (CAS 108-10-1)  
Ethyl benzene (CAS 100-41-4)  
n-butyl acetate (CAS 123-86-4)  
Silicon dioxide (CAS 7631-86-9)  
Talc (CAS 14807-96-6)  
Titanium dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
VM & P NAPHTHA (CAS 8032-32-4)  
Xylene (CAS 1330-20-7)

**US. Rhode Island RTK**

1,2-Dimethylbenzene (CAS 95-47-6)  
4-Methyl-2-pentanone (CAS 108-10-1)  
Ethyl benzene (CAS 100-41-4)  
n-butyl acetate (CAS 123-86-4)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

|                                     |                           |
|-------------------------------------|---------------------------|
| 4-Methyl-2-pentanone (CAS 108-10-1) | Listed: November 4, 2011  |
| Carbon Black (CAS 1333-86-4)        | Listed: February 21, 2003 |
| Ethyl benzene (CAS 100-41-4)        | Listed: June 11, 2004     |
| Formaldehyde (CAS 50-00-0)          | Listed: January 1, 1988   |
| Silicon dioxide (CAS 14808-60-7)    | Listed: October 1, 1988   |
| Titanium dioxide (CAS 13463-67-7)   | Listed: September 2, 2011 |

**US - California Proposition 65 - CRT: Listed date/Developmental toxin**

|                                     |                         |
|-------------------------------------|-------------------------|
| 4-Methyl-2-pentanone (CAS 108-10-1) | Listed: March 28, 2014  |
| Toluene (CAS 108-88-3)              | Listed: January 1, 1991 |

**US - California Proposition 65 - CRT: Listed date/Female reproductive toxin**

|                        |                        |
|------------------------|------------------------|
| Toluene (CAS 108-88-3) | Listed: August 7, 2009 |
|------------------------|------------------------|

**International Inventories**

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)                     | No                     |
| Canada               | Domestic Substances List (DSL)   | No                     |
| Canada               | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC)             | No                     |
| Europe               | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe               | European List of Notified Chemical Substances (ELINCS)                 | No                     |

| Country(s) or region        | Inventory name  | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)          | No                     |
| Korea                       | Existing Chemicals List (ECL)                                     | No                     |
| New Zealand                 | New Zealand Inventory   | No                     |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                     | No                     |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

|                      |   |
|----------------------|---|
| <b>Issue date</b>    | 06-15-2015  |
| <b>Version #</b>     | 01  |
| <b>HMIS® ratings</b> | Health: 3*<br>Flammability: 3<br>Physical hazard: 0   |
| <b>NFPA ratings</b>  | Health: 3<br>Flammability: 3<br>Instability: 0  |
| <b>Disclaimer</b>    | The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses. |