

## \*\*\*\*\* SECTION 1: PRODUCT IDENTIFICATION \*\*\*\*\*

MANUFACTURERS ADDRESS : 1101 THIRD STREET SOUTH, MINNEAPOLIS, MN 55415  
MFG TELEPHONE NUMBER : (612) 332-7371  
24 HR EMERGENCY PHONE NO : 1-888-345-5732  
CHEMICAL NAME OR FAMILY : PAINT PRODUCT  
FORMULA : NOT APPLICABLE  
TRADE NAME : 56 6476G AM EQ/IMP GLS WHITE  
REVISION DATE : 12-01-00 DATE PRINTED : 05-21-01

## \*\*\*\*\* SECTION 2: HAZARDOUS INGREDIENTS \*\*\*\*\*

NAME	APPROX WT %	
COMMON(NA):MINERAL SPIRITS	30-35%	TLV TWA 100.00 PPM TLV STEL NOT ESTAB OSHA PEL 500.00 PPM CEILING NOT ESTAB RECOMND NOT ESTAB
CAS:64742-47-8 CHEMICAL: DISTILLATES (PETROLEUM), HYDROTREATED LIGHT		
*COMMON( 1):ETHYLBENZENE	.1-1.0%	TLV TWA 100.00 PPM TLV STEL 125.00 PPM OSHA PEL 100.00 PPM CEILING NOT ESTAB RECOMND NOT ESTAB
CAS:100-41-4 CHEMICAL: BENZENE, ETHYL		
COMMON(NA):KAOLIN	5-10%	TLV TWA 10.00 MG/CU M TLV STEL NOT ESTAB OSHA PEL 15.00 MG/CU M CEILING NOT ESTAB RECOMND NOT ESTAB
CAS:1332-58-7 CHEMICAL: KAOLIN		
COMMON(NA):SILICA	1-5%	TLV TWA 10.00 MG/CU M TLV STEL NOT ESTAB OSHA PEL 6.00 MG/CU M CEILING NOT ESTAB RECOMND NOT ESTAB
CAS:112926-008 CHEMICAL: AMORPHOUS SILICA GEL		
COMMON(NA):TITANIUM DIOXIDE	20-25%	TLV TWA 10.00 MG/CU M TLV STEL NOT ESTAB OSHA PEL 10.00 MG/CU M CEILING NOT ESTAB RECOMND NOT ESTAB
CAS:13463-67-7 CHEMICAL: TITANIUM OXIDE		

CHEMICALS NOTED WITH A (\*) ARE REPORTABLE UNDER SECTION 313 OF SARA TITLE III

( 1) = THIS MATERIAL IS A CARCINOGEN PER IARC

ALL COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH U.S. TSCA CHEMICAL  
SUBSTANCE INVENTORY REQUIREMENTS.

## \*\*\*\*\* SECTION 3: PHYSICAL DATA \*\*\*\*\*

BOILING POINT: 315 DEG F. ( 157 DEG C.)  
VAPOR PRESSURE MM HG AT 68 DEG F. ( 20 DEG C.): 2.0  
VAPOR DENSITY (AIR = 1.0): 5.1  
SPECIFIC GRAVITY: 1.16  
PERCENT VOLATILE BY VOLUME: 52.76  
EVAPORATION RATE (BUTYL ACETATE = 1): .1  
SOLUBILITY IN WATER: NO  
APPEARANCE/ODOR: NORMAL FOR A COATINGS PRODUCT.  
PH : N.AV  
COEFFICIENT OF WATER/OIL DISTRIBUTION: N.AV

## \*\*\*\*\* SECTION 4: FIRE AND EXPLOSION HAZARD \*\*\*\*\*

FLASH POINT TCC/PM DEG F : 101  
FLASH POINT TCC/PM DEG C : 38  
LOWER EXPLOSIVE LIMIT : 1.00  
UPPER EXPLOSIVE LIMIT : 6.00  
AUTO IGNITION - DEG F : N.AV DEG C : N.AV  
SENSITIVITY TO IMPACT : NONE  
SENSITIVITY TO STATIC DISCHARGE : N.AV

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM, AND/OR WATER FOG.

SPECIAL FIRE FIGHTING PROCEDURES:  
FIRE FIGHTERS MUST WEAR SELF CONTAINED BREATHING APPARATUS OR AIR MASKS.  
CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY.UNUSUAL FIRE AND EXPLOSIVE HAZARDS:  
CONTAINS OXIDIZABLE MATERIALS. CONTAMINATED RAGS, WIPES, SAWDUST, ETC.  
MAY CATCH FIRE SPONTANEOUSLY. STORE WASTE IN WATER-FILLED, CLOSED METAL  
CONTAINERS UNTIL DISPOSED OF IN COMPLIANCE WITH ALL APPLICABLE REGULATIONS.

## \*\*\*\*\* SECTION 5: HEALTH HAZARD DATA \*\*\*\*\*

THRESHOLD LIMIT VALUE: NOT REQUIRED FOR MIXTURE.

## EFFECTS OF OVEREXPOSURE:

IMMEDIATE EFFECTS (ACUTE):  
HARMFUL IF INHALED. MAY AFFECT THE BRAIN, NERVOUS SYSTEM OR RES-  
PIRATORY SYSTEM, CAUSING DIZZINESS, HEADACHE, NAUSEA OR RESPIRATORY  
IRRITATION.OVEREXPOSURE TO INGREDIENTS IN THIS PRODUCT MAY CAUSE NOSE AND  
THROAT IRRITATION, EYE IRRITATION, SKIN IRRITATION.

## DELAYED EFFECTS (CHRONIC):

NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL  
OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM  
DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND  
INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.CONTAINS ETHYLBENZENE, WHICH HAS BEEN DETERMINED BY NTP TO BE AN  
ANIMAL CARCINOGEN WITH NO KNOWN RELEVANCE TO HUMANS. IARC HAS  
CLASSIFIED ETHYLBENZENE AS POSSIBLY CARCINOGENIC TO HUMANS (2B) ON  
THE BASIS OF SUFFICIENT EVIDENCE OF CARCINOGENICITY IN LABORATORY  
ANIMALS BUT INADEQUATE EVIDENCE FOR CANCER IN HUMANS.MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE - ANY  
RESPIRATORY OR SKIN CONDITION.

## EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15  
MINUTES AND GET MEDICAL ATTENTION.

SKIN CONTACT: WASH THOROUGHLY WITH SOAP AND WATER.

INHALATION: IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE  
TO FRESH AIR.

SWALLOWING: IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY.

POSSIBLE ROUTES OF ENTRY: INHALATION, INGESTION, SKIN ABSORPTION.

## \*\*\*\*\* SECTION 6: REACTIVITY DATA \*\*\*\*\*

THIS PRODUCT IS STABLE  
CONDITIONS TO AVOID: NONE  
INCOMPATIBILITY: STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION PRODUCTS:  
SILICON DIOXIDE CARBON DIOXIDE/MONOXIDE METAL OXIDES

HAZARDOUS POLYMERIZATION: NONE

\*\*\*\*\* SECTION 7: SPILL OR LEAK PROCEDURES \*\*\*\*\*

VENTILATE AREA. AVOID BREATHING OF VAPORS. USE SELF-CONTAINED BREATHING APPARATUS OR AIRMASK FOR LARGE SPILLS IN A CONFINED AREA. WIPE UP OR ABSORB ON SUITABLE MATERIAL AND SHOVEL UP. AVOID CONTACT WITH EYES.

WASTE DISPOSAL METHOD:  
DISPOSE IN CHEMICAL DISPOSAL AREA OR IN A MANNER THAT COMPLIES WITH LOCAL, STATE, PROVINCIAL AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

\*\*\*\*\* SECTION 8: SPECIAL PROTECTION INFORMATION \*\*\*\*\*

RESPIRATORY PROTECTION:  
UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ABOVE APPLICABLE LIMITS, NO RESPIRATOR IS REQUIRED. IF RESPIRATOR IS REQUIRED, THE APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) SHOULD BE WORN DURING APPLICATION. FOLLOW RESPIRATOR MANUFACTURERS DIRECTIONS FOR RESPIRATOR USE.

VENTILATION:  
REQUIRED FOR SPRAYING OR IN A CONFINED AREA, VENTILATION EQUIPMENT SHOULD BE EXPLOSION PROOF.

PROTECTIVE GLOVES: USUAL HAND PROTECTION FOR PAINT APPLICATION.  
EYE PROTECTION: FOR SPRAY APPLICATION, USE CHEMICAL GOGGLES AS A MINIMUM. OTHERWISE, USE SAFETY GLASSES WITH SIDE SHIELDS AS A MINIMUM.  
OTHER PROTECTIVE EQUIPMENT: USUAL CLOTHING FOR PAINTING OPERATIONS.

\*\*\*\*\* SECTION 9: SPECIAL PRECAUTIONS \*\*\*\*\*

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT STORE ABOVE 120 DEG F. ( 49 DEG C.) BASED ON THE PRODUCT FLASH POINT AND VAPOR PRESSURE, SUITABLE STORAGE SHOULD BE PROVIDED IN ACCORDANCE WITH OSHA REGULATION 1910.106/ONTARIO OH&S REGULATION 851 SECTION 22. EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE, INCLUDING FLAMMABLE OR EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR CONTAINER. ALL LABEL WARNINGS MUST BE OBSERVED UNTIL THE CONTAINER HAS BEEN CLEANED OR RECONDITIONED.

ABBREVIATIONS USED:

OSHA-OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION;  
IARC-INTERNATIONAL AGENCY FOR RESEARCH ON CANCER; LEL-LOWER EXPLOSIVE LIMITS;  
UEL-UPPER EXPLOSIVE LIMITS; MG CU M-MILLIGRAMS PER METERS CUBED; MM-MILLIMETERS;  
MPPCF-MILLIONS OF PARTICLES PER CUBIC FOOT; MSHA-MINE SAFETY AND HEALTH  
ADMINISTRATION; NIOSH-NATIONAL INSTITUTE OF OCCUPATIONAL SAFETY AND HEALTH;  
WHMIS-WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION SYSTEM; H-HOURS; HR-HOURS;  
NA-NOT APPLICABLE; NOT EST-NOT ESTABLISHED; NTP-NATIONAL TOXICOLOGY PROGRAM;  
PB-LEAD; PEL-PERMISSIBLE EXPOSURE LEVEL; PPM-PARTS PER MILLION;  
TCC/PM-TAG CLOSED CUP/PENSKY-MARTEN; RECM-RECOMMENDED; TLV-THRESHOLD LIMIT VALUES.  
N.AV-NOT AVAILABLE; N.AP-NOT APPLICABLE; C-CELSIUS; F-FAHRENHEIT

\*\*\*\*\* PREPARED BY SECTION \*\*\*\*\*

PREPARED BY: REGULATORY AFFAIRS DEPT.  
MFG TELEPHONE NUMBER : (612) 332-7371  
REVISION DATE : 12-01-00  
DATE PRINTED : 05-21-01

\*\*\*\*\* DISCLAIMER SECTION \*\*\*\*\*

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. THE VALSPAR CORPORATION MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA. THE VALSPAR CORPORATION FURTHER ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS, OR THIRD PARTIES CAUSED BY THIS MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THIS MATERIAL.