

## Wet Look

High solids catalyst to enhance acrylic enamel gloss and durability. Wet Look offers a super high gloss finish that's more durable and chemical resistant than conventional enamel finishes. Add to conventional acrylic enamel paints for higher gloss and increased durability.



<b>Part #</b>	<b>Description</b>	<b>Size</b>
<b>8105</b>	<b>Acrylic Enamel Hardener</b>	<b>1/4 Pint</b>
<b>8108</b>	<b>Acrylic Enamel Hardener</b>	<b>Pint</b>



### Substrates & Prep

Surface must be primed and or sealed and ready for paint.  
 Always clean surface with wax & grease remover prior to painting.



### Mixing

Typically 8:4:1 (8 Parts Acrylic Enamel Color : 4 Part Enamel Reducer : 1 Part Wet Look Hardener)  
 Note: Follow paint manufacturers reduction ratio. Some paints come partially reduced from manufacturer.



### Drying

Flash Time 10-15 minutes  
 Dust Free 10 minutes  
 Tack Free 1 hour  
 Sand/Recoat Overnight to 48 hours  
 Pot Life Typically 4 - 6 hours



### Master Tips

Due to large variance in reducer temperature ranges, above figures are typical of performance when proper temperature reducer is used. Always add catalyst slowly to reduced paint. Adding catalyst to quickly or to unreduced paint can cause the paint to shock.